

CINDOLUBE 4683

Neat Aluminium Forming Oil

DESCRIPTION

CINDOLUBE 4683 is based on hydro treated mineral oil with low aromatic content. A combination of polar additives provide the oil with high load carrying properties. The oil provides good surface finish of the machined work pieces.

CINDOLUBE 4683 is free from Chlorine, Sulphur, Phosphorous and heavy metals (Zinc)

APPLICATIONS

CINDOLUBE 4683 is used for drawing of aluminium wire and sheet material. The "ND" additives prevent the fresh machined surface from rapid oxidation.

CINDOLUBE 4683 shows also good results for aluminium press forming.

RECOMMENDATION FOR USE

CINDOLUBE 4683 is used neat as supplied.

TYPICAL PHYSICAL PROPERTIES

Colour	yellow	
Specific Gravity @ 20 °C kg/m ³	890	ASTM D 4052
Kinematic Viscosity @ 40°C, mm ² /s	145	ASTM D 7042
Flash Point COC °C	230	ASTM D 92
Pour Point °C	-15	ASTM D 99
Copper Corrosion	1b	ASTM D 130

BENEFITS

- Reduced cost - higher production rates due to strong lubricity
- Reduced cost - clean workshop environment due to less oil mist and evaporation
- Satisfied staff - good EHS profile, reduced smell and oil mist
- Satisfied staff - light color for good monitoring of the operation

RELATED PRODUCTS

For best results we recommend the use of the Houghton range of industrial lubricants, cleaners and corrosion protective.

For more information, please contact your local Houghton representative.

STORAGE

Please refer to section 7 of Safety Data Sheets for handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 40°C unless otherwise specified. Use stock in delivery rotation.

HEALTH AND SAFETY

Safety data sheets are available in accordance with Regulation (EC) No 1907/2006 Annex II where a substance or preparation meets the criteria in accordance with Directives 67/548/EEC or 1999/45/EC.

GM 0113 GB



HOUGHTON™

Houghton plc
Beacon Road, Trafford Park
Manchester M17 1AF

Tel +44 (0) 161 874 5000
Fax +44 (0) 161 874 5001
E-mail uk.enquiries@houghtoneurope.com
<http://www.houghtonintl.com>

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.