HOUGHTO-CLEAN 121

(Formerly HOUGHTO-CLEAN UF 7)

Aqueous Neutral Hard Surface Cleaner

DESCRIPTION

HOUGHTO-CLEAN 121 is a neutral multi purpose hard surface cleaner

APPLICATIONS

HOUGHTO-CLEAN 121 can be applied by immersion, manual cleaning techniques, cold and heated lance pressure washers and by automated floor cleaning equipment to remove light oils and general soiling for cleaning detergent resistant surfaces.

RECOMMENDATION FOR USE

Temperature = 20 to 80°C

Concentration = up to 10% v/v for manual cleaning Concentration = as required for immersion cleaning Concentration = up to 10% v/v for lance pressure washers Concentration = up to 15% v/v for floor cleaning

TYPICAL PHYSICAL PROPERTIES

Appearance	Light yellow liquid
Specific Gravity	1.03
pH in Use	Typically 7 - 8
Refractometer Factor	7.5

BENEFITS

- Neutral pH for compatibility with most substrates
- Neutral pH enables easier disposal of used solutions
- Leaves no powdery deposits on cleaned surfaces
- Multifunctional applications for reduced product inventory

RELATED PRODUCTS

Houghton is a market leader in the development and supply of manufacturing process fluids. The HOUGHTO-CLEAN range of industrial cleaners have been developed to compliment and work synergistically with these and particularly with our machining, forming, quenching and similar products.

For more information, please contact your local Houghton representative.

STORAGE

Please refer to section 7 of Safety Data Sheets for handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 40°C unless otherwise specified. Use stock in delivery rotation.

HEALTH AND SAFETY

Safety data sheets are available in accordance with Regulation (EC) No 1907/2006 Annex II where a substance or preparation meets the criteria in accordance with Directives 67/548/EEC or 1999/45/EC.

KP 2012/10/02 GB



Houghton plc Beacon Road, Trafford Park Manchester M17 1AF Tel +44 (0) 161 874 5000 Fax +44 (0) 161 874 5001 E-mail uk.enquiries@houghtoneurope.com http://www. Houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.