

FENELLA FLUID D 2628

Soluble Cold Deformation Oil

DESCRIPTION

FENELLA FLUID D 2628 is an ester based water soluble oil for drawing operations and contains special EP lubricity additives and corrosion inhibitors.

FENELLA FLUID D 2628 is free of bactericide and fungicide. It is also free from Chlorine.

APPLICATIONS

FENELLA FLUID D 2628 is a soluble oil which can be used for extreme drawing operations.

FENELLA FLUID D 2628 has extremely high EP and lubricity properties, so high alloyed steels and stainless steels can be worked

RECOMMENDATION FOR USE

FENELLA FLUID D 2628 is used neat as supplied or diluted with water in concentration between 5 and 50%

TYPICAL PHYSICAL PROPERTIES

Colour	brown	
Specific Gravity @ 20 °C kg/m ³	980	ASTM D 4052
Kinematic Viscosity @ 40°C, mm ² /s	410	ASTM D 7042
pH @ 5%	8.4	DIN 51396
Corrosion protection Note 0 @ %	5	DIN 51360/2
Refractometer factor	1.0	

BENEFITS

- Reduced cost - higher production rates due to strong lubricity
- Reduced cost - clean workshop environment due to less oil mist and evaporation
- Satisfied staff - good EHS profile, reduced smell and oil mist
- Reduced cost - easy to be washed off with standard cleaners

RELATED PRODUCTS

For best results we recommend the use of the Houghton range of industrial lubricants, cleaners and corrosion protective.

For more information, please contact your local Houghton representative.

STORAGE

Please refer to section 7 of Safety Data Sheets for handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 40°C unless otherwise specified. Use stock in delivery rotation.

HEALTH AND SAFETY

Safety data sheets are available in accordance with Regulation (EC) No 1907/2006 Annex II where a substance or preparation meets the criteria in accordance with Directives 67/548/EEC or 1999/45/EC.

GM 0113 GB



Houghton plc
Beacon Road, Trafford Park
Manchester M17 1AF

Tel +44 (0) 161 874 5000
Fax +44 (0) 161 874 5001
E-mail uk.enquiries@houghtoneurope.com
<http://www.houghtonintl.com>

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.