

# FENELLA OIL BSD 210 N

Neat Oil for Cold Extrusion

## DESCRIPTION

FENELLA OIL BSD 210 N is based on hydro treated mineral oil with low aromatic content. A combination of polar, extreme pressure and anti-wear additives provide the oil with high load carrying properties. The oil provides good surface finish of the machined work pieces.

FENELLA OIL BSD 210 N is free from Chlorine and heavy metals (Zinc)

## APPLICATIONS

FENELLA OIL BSD 210 N is a dual purpose cold extrusion oil which can be used as well for the machine lubrication.

FENELLA OIL BSD 210 N is used for easy machinable materials.

## RECOMMENDATION FOR USE

FENELLA OIL BSD 210 N is used neat as supplied.

## TYPICAL PHYSICAL PROPERTIES

Colour	amber	
Specific Gravity @ 20 °C kg/m <sup>3</sup>	880	ASTM D 4052
Kinematic Viscosity @ 40°C, mm <sup>2</sup> /s	100	ASTM D 7042
Flash Point COC °C	230	ASTM D 92
Pour Point °C	-12	ASTM D 99
Copper Corrosion	1b	ASTM D 130

## BENEFITS

- Reduced cost - longer sump life from selected raw material
- Reduced cost - less energy consumption due to high EP and lubricity
- Satisfied staff - good EHS profile, free from Chlorine and other suspect substances.
- Simplified storage - multi purpose oil for machine lubrication and cold deformation.

## RELATED PRODUCTS

For best results we recommend the use of the Houghton range of industrial lubricants, cleaners and corrosion protective.

For more information, please contact your local Houghton representative.

## STORAGE

Please refer to section 7 of Safety Data Sheets for handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 40°C unless otherwise specified. Use stock in delivery rotation.

## HEALTH AND SAFETY

Safety data sheets are available in accordance with Regulation (EC) No 1907/2006 Annex II where a substance or preparation meets the criteria in accordance with Directives 67/548/EEC or 1999/45/EC.

GM 0113 GB



Houghton plc  
Beacon Road, Trafford Park  
Manchester M17 1AF

Tel +44 (0) 161 874 5000  
Fax +44 (0) 161 874 5001  
E-mail [uk.enquiries@houghtoneurope.com](mailto:uk.enquiries@houghtoneurope.com)  
<http://www.houghtonintl.com>

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.