

METALINA D 299

Water soluble metalworking fluid

DESCRIPTION

METALINA D 299 is a fully synthetic grinding fluid with a high quality corrosion inhibiting additive package. The mineral oil-free, transparent solution provides long sump life and excellent tramp oil rejection.

APPLICATIONS

METALINA D 299 is recommended for surface and cylindrical grinding of ferrous materials including cast iron.

The synthetic formula completely rejects tramp oil for cleanliness in use and provides extremely low foam, maximum filtration efficiency and rapid fines separation.

The product is designed primarily for soft water.

RECOMMENDATION FOR USE

Ferrous grinding 4-7 %

TYPICAL PHYSICAL PROPERTIES

<i>Concentrate Appearance</i>	<i>Transparent yellow fluid</i>
<i>Specific Gravity @ 20°C</i>	<i>1.07</i>
<i>Refractometer Factor</i>	<i>2.9</i>
<i>Emulsion Appearance</i>	<i>Transparent colourless</i>
<i>pH in Use</i>	<i>8.9-9.6</i>

BENEFITS

- Rejects tramp oil completely - Excellent component visibility with no spoilage of coolant
- Outstanding low foam - no antifoam treatments necessary
- Good detergency – for extended wheel life and improved surface finish.
- Good corrosion protection - lower reject rate and less machine maintenance
- Rapid fines separation - excellent filterability with extended filter life
- Mineral oil, formaldehyde, chlorine, secondary amines and phenol-free - very good EHS profile

RELATED PRODUCT

Water soluble coolants are complemented by our full range of high quality, speciality production fluids including energy saving wash chemicals, low misting neat cutting oils, non-VOC rust preventives and long life heat treatment fluids. Fluidcare services complete our value added portfolio with a range of expert services and equipment to help reduce costs and improve productivity. For more information, please contact your local Houghton representative.

STORAGE

Please refer to section 7 of Safety Data Sheets for handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 40°C unless otherwise specified. Use stock in delivery rotation.

HEALTH AND SAFETY

Safety data sheets are available in accordance with Regulation (EC) No 1907/2006 Annex II where a substance or preparation meets the criteria in accordance with Directives 67/548/EEC or 1999/45/EC.

RF19/09/2012GB



Houghton plc
Beacon Road, Trafford Park
Manchester M17 1AF

Tel +44 (0) 161 874 5000
Fax +44 (0) 161 874 5001
E-mail uk.enquiries@houghtoneurope.com
<http://www.houghtonintl.com>

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.