

THERMEX WW 530

Water miscible synthetic hot forging lubricant (graphite free)

DESCRIPTION

THERMEX WW 530 is a high performance water based synthetic solution, free from graphite and mineral oils that forms a clear solution in water which forms a white lubricating film on the die.

APPLICATIONS

THERMEX WW 530 is used for forging of carbon steel alloys and is particularly suitable as a release agent for all operations where low die forging temperatures occur. Die temperatures should typically be between 120°C – 250°C.

RECOMMENDATION FOR USE

The concentration of THERMEX WW 530 is adjusted depending on the degree of difficulty and amount of deformation.

- Simple forgings 3-10%
- Moderate forgings 5 - 10 %
- Severe forgings 10 - 40 %

TYPICAL PHYSICAL PROPERTIES

Appearance	Clear liquid	
Specific gravity @ 20°C	1.18	ASTM D 1298
pH	7.8	DIN 51396
Kinematic Viscosity 20°C mm ² /s	73	IP 71/DIN 51562

BENEFITS

- Reduces costs and increases productivity - excellent forming properties, good release, reduces wear on the dies, low foaming, clean surfaces on the metal surface after forging reduce subsequent cleaning operations. Reduces the heat transmission between the die block and billet.
- Easy to use - easy to mix with water and control with a refractometer, forms a stable solution that uniformly wets the die surface.
- Operator and Environmentally friendly - graphite and oil free for a clean working environment. Ammonia free for a pleasant working environment.

ADDITIONAL PRODUCT DATA

It is recommended that dilutions are made with suitable mixing equipment. If manually mixing, add water slowly to the product while mixing for best results.

RELATED PRODUCTS

Houghton specialises in products and services for Heat Treatment, Machining and Grinding, Cleaning, and Fire Resistant Hydraulic Fluids and Industrial Lubricants. For more information, please contact your local Houghton representative.

STORAGE

Please refer to section 7 of Safety Data Sheets for handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 40°C unless otherwise specified. Use stock in delivery rotation.

HEALTH AND SAFETY

Safety data sheets are available in accordance with Regulation (EC) No 1907/2006 Annex II where a substance or preparation meets the criteria in accordance with Directives 67/548/EEC or 1999/45/EC.

GT 2013/11/08 GB



HOUGHTON™

Houghton plc
Beacon Road, Trafford Park
Manchester M17 1AF

Tel +44 (0) 161 874 5000
Fax +44 (0) 161 874 5001
E-mail
uk.enquiries@houghtoneurope.com
<http://www.houghtonintl.com>

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.