

MACRON 2425 S-8

Neat Cutting and Grinding Oil

DESCRIPTION

MACRON 2425 S-8 is based on HC hydro crack base oil technology with very low aromatic content. A combination of polar, extreme pressure and anti-wear additives provide the oil with high load carrying properties. The oil provides good surface finish of the machined work pieces.

MACRON 2425 S-8 is free from Chlorine and heavy metals (Zinc)

APPLICATIONS

MACRON 2425 S-8 is a high performance grinding oil, used for flute grinding on high-speed steel, and with ceramic and diamond or boron nitride grinding wheels.

MACRON 2425 S-8 can also be used for grinding spiral toothed bevel gears and flat or cylindrical grinding processes, on the complete range of steels and non-ferrous metals.

RECOMMENDATION FOR USE

MACRON 2425 S-8 is used neat as supplied.

TYPICAL PHYSICAL PROPERTIES

Colour	yellow	
Specific Gravity @ 20 °C kg/m ³	830	ASTM D 4052
Kinematic Viscosity @ 40°C, mm ² /s	8	ASTM D 7042
Flash Point COC °C	170	ASTM D 92
Pour Point °C	-18	ASTM D 97
Copper Corrosion	1b	ASTM D 130

BENEFITS

- Reduced cost - improved tool life due to high EP power
- Reduced cost - higher production rates due to strong lubricity
- Reduced cost - less energy consumption due to high EP and lubricity
- Peace of mind - approved by leading MTM (machine tool manufacturer)

RELATED PRODUCTS

For best results we recommend the use of the Houghton range of industrial lubricants, cleaners and corrosion protective.

For more information, please contact your local Houghton representative.

STORAGE

Please refer to section 7 of Safety Data Sheets for handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 40°C unless otherwise specified. Use stock in delivery rotation.

HEALTH AND SAFETY

Safety data sheets are available in accordance with Regulation (EC) No 1907/2006 Annex II where a substance or preparation meets the criteria in accordance with Directives 67/548/EEC or 1999/45/EC.

GM 18/09/2012 GB



Houghton plc
Beacon Road, Trafford Park
Manchester M17 1AF

Tel +44 (0) 161 874 5000
Fax +44 (0) 161 874 5001
E-mail uk.enquiries@houghtoneurope.com
<http://www.houghtonintl.com>

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.