

# RUST VETO 100 D

Medium Term - Dewatering - Rust Preventive [ISO 6743-8 RD]

## DESCRIPTION

RUST VETO 100 D is a blend of mineral oil, and carefully selected performance additives which provide up to 6 months indoor protection.

RUST VETO 100 D is a premium quality dewatering rust preventive and exhibits a very thin oily film, which is self-healing, resists peeling and cracking, neutralizes fingerprints and is easily removed if required.

RUST VETO 100 D is effective on ferrous and non-ferrous metal. It contains oils with a very low level of PCA, exceeding regulation expectation, and is barium free.

## APPLICATIONS

RUST VETO 100 D provides medium term protection, inter-operational and final protection, on :

- o (semi)-finished automotive and machinery components like valves, gears, camshaft, box, bearing, chains, motor, fasteners, braking system, precision components with highly finished surfaces ...
- o Phosphated or blackened surfaces by filling the micro porosity.
- o Finely machined or ground metal surfaces such as valves, rollers and fasteners.
- o Steel tubes after pickling and washing processes, thank to its good penetration into bundle.

Dewatering applications in areas where the use of flammable solvents is prohibited.

The residual thin oily film don't need to be removed before assembly in most case and it can act to enhance lubrication properties in the deformation and manipulation process for light applications.

## TYPICAL PHYSICAL PROPERTIES

<i>Appearance</i>	<i>clear yellow to orange</i>
<i>Specific Gravity</i>	<i>0.82</i>
<i>Flash Point (°C) open cup</i>	<i>138</i>
<i>Viscosity @40°C (cSt)</i>	<i>6</i>
<i>Film Thickness (µm)</i>	<i>&lt; 2</i>

## BENEFITS

- o Economic - Solvent free technology, avoid CAPEX investment in solvent vapour collection and treatment
- o Economic - Very performing thin film compatible with most of lubricant oil, no need to wash off.
- o Operator friendly - High flash points and low volatility to minimize fire risk in application transportation and storage.
- o Operator friendly - No heavy metal such as barium
- o Quality - Neutralizing fingerprints in case of accidental bare handling
- o Quality - High performing chemistry which keep your added value safe and reduce re-work risk

## RECOMMENDATION FOR USE

RUST VETO 100 D is used neat as supplied.

For more information please consult our recommendation book and selection guide.

## RELATED PRODUCTS

Product is compatible with the full range of Houghton's portfolio, esp. with the Houghto-Clean for post degreasing when required and most of our metal working fluid (Hocut, Adrana, Macron, Cut-Max, ...)

For more information, please contact your local Houghton Representative.

## STORAGE

Please refer to section 7 of Safety Data Sheets for handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 40°C unless otherwise specified. Use stock in delivery rotation.

## HEALTH AND SAFETY

Safety data sheets are available in accordance with Regulation (EC) No 1907/2006 Annex II where a substance or preparation meets the criteria in accordance with Directives 67/548/EEC or 1999/45/EC.

FB21/09/2012GB



**HOUGHTON™**

Houghton plc  
Beacon Road, Trafford Park  
Manchester M17 1AF

Tel +44 (0) 161 874 5000  
Fax +44 (0) 161 874 5001  
E-mail [uk.enquiries@houghtoneurope.com](mailto:uk.enquiries@houghtoneurope.com)  
<http://www.houghtonintl.com>

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.