

# RUST VETO 14

Long Term - Rust Preventive [ISO 6743-8 RP]

## DESCRIPTION

RUST VETO 14 is a blend of desaromatised solvent, and carefully selected performance additives which provide up to 18 months indoor protection and several months outdoor protection.

RUST VETO 14 is a premium quality rust preventive and exhibits a thin hard, dry to the touch resin-like film, which resists flaking and cracking, and can be removed if required.

RUST VETO 14 is effective on ferrous and non-ferrous metal. It is Barium free.

## APPLICATIONS

RUST VETO 14 provides long term protection and final protection, on :

- Materials and equipment during shipment overseas, when properly packed.
- Materials and equipment which are subjected to hostile conditions eg. Coastal and Marine environments.
- Drill pipe and casing in outdoor coastal locations.
- Steel structures during operation or storage periods. Particularly resisting to carry-over of alkaline grinding coolants, soluble oil emulsions and acidic rinse water atmosphere.

## TYPICAL PHYSICAL PROPERTIES

<i>Appearance</i>	<i>Clear brown</i>
<i>Specific Gravity</i>	<i>0,87</i>
<i>Flash Point (°C) closed cup</i>	<i>65</i>
<i>Film Thickness (µm)</i>	<i>&lt; 7</i>

## BENEFITS

- Economic - Fast drying, increase production speed.
- Operator friendly - Desaromatised solvent, No heavy metal such as Barium
- Operator friendly - Dry film free from tackiness, more pleasant to handle. Will not rub off on cartons or packages
- Environmentally friendly - Medium flash point which limits evaporation and fire risk
- Security - Excellent rust prevention even under severe condition.
- Security - High performing chemistry which keep your added value safe and reduce re-work risk

## RECOMMENDATION FOR USE

RUST VETO 14 is used neat as supplied. We recommend to mix or agitate prior use.

For more information please consult our recommendation book and selection guide.

## RELATED PRODUCTS

Product is compatible with the full range of Houghton's portfolio, esp. with the Houghto-Clean for post degreasing when required and most of our metal working fluid (Hocut, Adrana, Macron, Cut-Max, ...)

For details please conduct your local Technical Service.

## STORAGE

Please refer to section 7 of Safety Data Sheets for handling and storage information, including product shelf life. Product should be stored under cover in clean, dry conditions and protected from frost. Recommended storage temperature is usually between 5°C and 25°C unless otherwise specified. Use stock in delivery rotation.

## HEALTH AND SAFETY

Safety data sheets are available in accordance with Regulation (EC) No 1907/2006 Annex II where a substance or preparation meets the criteria in accordance with Directives 67/548/EEC or 1999/45/EC.

FB 31/07/2013 GB



**HOUGHTON™**

Houghton plc  
Beacon Road, Trafford Park  
Manchester M17 1AF

Tel +44 (0) 161 874 5000  
Fax +44 (0) 161 874 5001  
E-mail  
uk.enquiries@houghtoneurope.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.